

مواصفات موقع القطرانة

Ref	TYPE	Descriptions	Qty.
A	Outdoor Color Camera 8MP	<ul style="list-style-type: none"> •8 MP Fixed-focal Bullet Network Camera •1/1.8" CMOS image sensor, low luminance, and high-definition image. •Max. IR LEDs Length 30 m •4 mm Fixed-Focal lens •ROI, SMART H.264+/H.265+, flexible coding, applicable to various bandwidth and storage environments. •Smart intrusion prevention, include cross line, intrusion •Color technology ISP AI ensures 24-hour full-color images 120dB true WDR technology enables clear image in strong light scene •Rotation mode, WDR, 3D NR, HLC, BLC, digital watermarking, applicable to various monitoring scenes. •Intelligent monitoring: Intrusion, tripwire (the two functions support the classification and accurate detection of vehicle and human). •Color: 0.0005 lux (F1.0, AGC ON) 	8
B	Indoor Color Camera 5MP	<ul style="list-style-type: none"> •5 MP Fixed-focal Bullet Network Camera •1/1.8" CMOS image sensor, low luminance, and high-definition image. •Max. IR LEDs Length 30 m •2.8 mm Fixed-Focal lens •ROI, SMART H.264+/H.265+, flexible coding, applicable to various bandwidth and storage environments. •Smart intrusion prevention, include cross line, intrusion •Color technology ISP AI ensures 24-hour full-color images 120dB true WDR technology enables clear image in strong light scene •Rotation mode, WDR, 3D NR, HLC, BLC, digital watermarking, applicable to various monitoring scenes. •Intelligent monitoring: Intrusion, tripwire (the two functions support the classification and accurate detection of vehicle and human). •Color: 0.0005 lux (F1.0, AGC ON) 	3
C	NVR 16Ch	<ul style="list-style-type: none"> •Support 265+/H.265/H.264 video formats •16-channel input / 2SATA up to 8Tera. •decoding capability: 8 × 4K@30 fps. Max 16 × 1080@30 fps. •Max. 300Mbps incoming bandwidth. •Support mainstream cameras of ONVIF conformance (Profile S, Profile G, Profile T) and RTSP protocols •VGA and HDMI independent output •Up to 16 Megapixels resolution recording •ANR technology to enhance the storage reliability when the network is disconnected •Support cloud upgrade <p>HDD WD PURPLE 10TB INTERNAL</p>	1

D	Switch PoE 8 Port	<ul style="list-style-type: none"> • Switch unmanaged 8 port PoE, 2 port uplink . • 1 Giga speed for all ports • Switching capacity 18 Gbps • Supports PoE Power up to 30W for each PoE port. • Supports PoE Power up to 200W . • Line-speed forwarding, intelligent identification 	2
E	Network Bridge	<ul style="list-style-type: none"> • 802.11ac for up to 867Mbps on 5GHz wireless data rate • 23dBi high-gain directional 2x2 MIMO, ideal for long-distance application • Excellent beam directivity, improved latency and noise cancellation • Innovative snap-lock parts make for fast assembly and a sturdy structural design keeps CPE710 stable even in strong winds • Durable IP65 weatherproof enclosure along with 15kV ESD and 6kV lightning protection ensures all-weather suitability • Pharos Control gives administrators a free, centralized management system • Passive PoE supports to allow flexible deployment and convenient installation 	2
F	Network Point Capling	CAT6A cable up to 1 Giga speed	350M
G	Pipes for cabling	PVC Pipes for network cable installation outdoor /indoor ..25mm	180M
J	Installation and programming	<p>installation pipes and cabling and camera , and system configuration / يشمل التحفير بالارض</p> <p>لتأسيس الكوابل لمسافة 60 متر والعمل حسب الاصول المدنية والانشائية .</p>	1

مواصفات موقع العقبة

Ref	TYPE	Descriptions	Qty.
A	Outdoor Color Camera 8MP	<ul style="list-style-type: none"> •8 MP Fixed-focal Bullet Network Camera •1/1.8" CMOS image sensor, low luminance, and high-definition image. •Max. IR LEDs Length 30 m •4 mm Fixed-Focal lens •ROI, SMART H.264+/H.265+, flexible coding, applicable to various bandwidth and storage environments. •Smart intrusion prevention, include cross line, intrusion •Color technology ISP AI ensures 24-hour full-color images 120dB true WDR technology enables clear image in strong light scene •Rotation mode, WDR, 3D NR, HLC, BLC, digital watermarking, applicable to various monitoring scenes. •Intelligent monitoring: Intrusion, tripwire (the two functions support the classification and accurate detection of vehicle and human). •Color: 0.0005 lux (F1.0, AGC ON) 	8
B	Indoor Color Camera 5MP	<ul style="list-style-type: none"> •5 MP Fixed-focal Bullet Network Camera •1/1.8" CMOS image sensor, low luminance, and high-definition image. •Max. IR LEDs Length 30 m •2.8 mm Fixed-Focal lens •ROI, SMART H.264+/H.265+, flexible coding, applicable to various bandwidth and storage environments. •Smart intrusion prevention, include cross line, intrusion •Color technology ISP AI ensures 24-hour full-color images 120dB true WDR technology enables clear image in strong light scene •Rotation mode, WDR, 3D NR, HLC, BLC, digital watermarking, applicable to various monitoring scenes. •Intelligent monitoring: Intrusion, tripwire (the two functions support the classification and accurate detection of vehicle and human). •Color: 0.0005 lux (F1.0, AGC ON) 	3
C	NVR 16Ch	<ul style="list-style-type: none"> •Support 265+/H.265/H.264 video formats •16-channel input / 2SATA up to 8Tera. •decoding capability: 8 × 4K@30 fps. Max 16 × 1080@30 fps. •Max. 300Mbps incoming bandwidth. •Support mainstream cameras of ONVIF conformance (Profile S, Profile G, Profile T) and RTSP protocols •VGA and HDMI independent output •Up to 16 Megapixels resolution recording •ANR technology to enhance the storage reliability when the network is disconnected •Support cloud upgrade HDD WD PURPLE 10TB INTERNAL 	1

D	Switch PoE 8 Port	<ul style="list-style-type: none"> • Switch unmanaged 8 port PoE, 2 port uplink . • 1 Giga speed for all ports • Switching capacity 18 Gbps • Supports PoE Power up to 30W for each PoE port. • Supports PoE Power up to 200W . • Line-speed forwarding, intelligent identification 	2
E	Network Bridge	<ul style="list-style-type: none"> • 802.11ac for up to 867Mbps on 5GHz wireless data rate • 23dBi high-gain directional 2x2 MIMO, ideal for long-distance application • Excellent beam directivity, improved latency and noise cancellation • Innovative snap-lock parts make for fast assembly and a sturdy structural design keeps CPE710 stable even in strong winds • Durable IP65 weatherproof enclosure along with 15kV ESD and 6kV lightning protection ensures all-weather suitability • Pharos Control gives administrators a free, centralized management system • Passive PoE supports to allow flexible deployment and convenient installation 	2
F	Network Point Capling	CAT6A cable up to 1 Giga speed	350M
G	Pipes for cabling	PVC Pipes for network cable installation outdoor /indoor ..25mm	180M
J	Installation and programming	<p>installation pipes and cabling and camera , and system configuration / يشمل التحفير بالارض</p> <p>لتأسيس الكوابل لمسافة 60 متر والعمل حسب الاصول المدنية والانشائية .</p>	1

مواصفات موقع أبو علندا

Ref	TYPE	Descriptions	Qty.
A	Outdoor Color Camera 8MP	<ul style="list-style-type: none"> •8 MP Fixed-focal Bullet Network Camera •1/1.8" CMOS image sensor, low luminance, and high-definition image. •Max. IR LEDs Length 30 m •4 mm Fixed-Focal lens •ROI, SMART H.264+/H.265+, flexible coding, applicable to various bandwidth and storage environments. •Smart intrusion prevention, include cross line, intrusion •Color technology ISP AI ensures 24-hour full-color images 120dB true WDR technology enables clear image in strong light scene •Rotation mode, WDR, 3D NR, HLC, BLC, digital watermarking, applicable to various monitoring scenes. •Intelligent monitoring: Intrusion, tripwire (the two functions support the classification and accurate detection of vehicle and human). •Color: 0.0005 lux (F1.0, AGC ON) 	8~10
B	Indoor Color Camera 5MP	<ul style="list-style-type: none"> •5 MP Fixed-focal Bullet Network Camera •1/1.8" CMOS image sensor, low luminance, and high-definition image. •Max. IR LEDs Length 30 m •2.8 mm Fixed-Focal lens •ROI, SMART H.264+/H.265+, flexible coding, applicable to various bandwidth and storage environments. •Smart intrusion prevention, include cross line, intrusion •Color technology ISP AI ensures 24-hour full-color images 120dB true WDR technology enables clear image in strong light scene •Rotation mode, WDR, 3D NR, HLC, BLC, digital watermarking, applicable to various monitoring scenes. •Intelligent monitoring: Intrusion, tripwire (the two functions support the classification and accurate detection of vehicle and human). •Color: 0.0005 lux (F1.0, AGC ON) 	3
C	NVR 16Ch	<ul style="list-style-type: none"> •Support 265+/H.265/H.264 video formats •16-channel input / 2SATA up to 10Tera. •decoding capability: 8 × 4K@30 fps. Max 16 × 1080@30 fps. •Max. 300Mbps incoming bandwidth. •Support mainstream cameras of ONVIF conformance (Profile S, Profile G, Profile T) and RTSP protocols •VGA and HDMI independent output •Up to 16 Megapixels resolution recording •ANR technology to enhance the storage reliability when the network is disconnected •Support cloud upgrade <p style="text-align: right;">HDD WD PURPLE 10TB INTERNAL</p>	1

D	Switch PoE 8 Port	<ul style="list-style-type: none"> • Switch unmanaged 8 port PoE, 2 port uplink . • 1 Giga speed for all ports • Switching capacity 18 Gbps • Supports PoE Power up to 30W for each PoE port. • Supports PoE Power up to 200W . • Line-speed forwarding, intelligent identification 	2
E	Network Bridge	<ul style="list-style-type: none"> • 802.11ac for up to 867Mbps on 5GHz wireless data rate • 23dBi high-gain directional 2x2 MIMO, ideal for long-distance application • Excellent beam directivity, improved latency and noise cancellation • Innovative snap-lock parts make for fast assembly and a sturdy structural design keeps CPE710 stable even in strong winds • Durable IP65 weatherproof enclosure along with 15kV ESD and 6kV lightning protection ensures all-weather suitability • Pharos Control gives administrators a free, centralized management system • Passive PoE supports to allow flexible deployment and convenient installation 	2
F	Network Point Cabling	CAT6A cable up to 1 Giga speed	150M
G	Pipes for cabling	PVC Pipes for network cable installation outdoor /indoor ..25mm	90M
J	DISPLAY	40 "" LED TV (very good quality)	1
H	Installation and programming	installation pipes and cabling and camera , and system configuration . حسب الأصول .	1

مواصفات موقع الرصيفة

Ref	TYPE	Descriptions	Qty.
A	Outdoor Color Camera 8MP	<ul style="list-style-type: none"> •8 MP Fixed-focal Bullet Network Camera •1/1.8" CMOS image sensor, low luminance, and high-definition image. •Max. IR LEDs Length 30 m •4 mm Fixed-Focal lens •ROI, SMART H.264+/H.265+, flexible coding, applicable to various bandwidth and storage environments. •Smart intrusion prevention, include cross line, intrusion •Color technology ISP AI ensures 24-hour full-color images 120dB true WDR technology enables clear image in strong light scene •Rotation mode, WDR, 3D NR, HLC, BLC, digital watermarking, applicable to various monitoring scenes. •Intelligent monitoring: Intrusion, tripwire (the two functions support the classification and accurate detection of vehicle and human). •Color: 0.0005 lux (F1.0, AGC ON) 	8
B	Indoor Color Camera 5MP	<ul style="list-style-type: none"> •5 MP Fixed-focal Bullet Network Camera •1/1.8" CMOS image sensor, low luminance, and high-definition image. •Max. IR LEDs Length 30 m •2.8 mm Fixed-Focal lens •ROI, SMART H.264+/H.265+, flexible coding, applicable to various bandwidth and storage environments. •Smart intrusion prevention, include cross line, intrusion •Color technology ISP AI ensures 24-hour full-color images 120dB true WDR technology enables clear image in strong light scene •Rotation mode, WDR, 3D NR, HLC, BLC, digital watermarking, applicable to various monitoring scenes. •Intelligent monitoring: Intrusion, tripwire (the two functions support the classification and accurate detection of vehicle and human). •Color: 0.0005 lux (F1.0, AGC ON) 	3
C	NVR 16Ch	<ul style="list-style-type: none"> •Support 265+/H.265/H.264 video formats •16-channel input / 2SATA up to 8Tera. •decoding capability: 8 × 4K@30 fps. Max 16 × 1080@30 fps. •Max. 300Mbps incoming bandwidth. •Support mainstream cameras of ONVIF conformance (Profile S, Profile G, Profile T) and RTSP protocols •VGA and HDMI independent output •Up to 16 Megapixels resolution recording •ANR technology to enhance the storage reliability when the network is disconnected •Support cloud upgrade HDD WD PURPLE 10TB INTERNAL 	1

D	Switch PoE 8 Port	<ul style="list-style-type: none"> • Switch unmanaged 8 port PoE, 2 port uplink . • 1 Giga speed for all ports • Switching capacity 18 Gbps • Supports PoE Power up to 30W for each PoE port. • Supports PoE Power up to 200W . • Line-speed forwarding, intelligent identification 	2
E	Network Bridge	<ul style="list-style-type: none"> • 802.11ac for up to 867Mbps on 5GHz wireless data rate • 23dBi high-gain directional 2x2 MIMO, ideal for long-distance application • Excellent beam directivity, improved latency and noise cancellation • Innovative snap-lock parts make for fast assembly and a sturdy structural design keeps CPE710 stable even in strong winds • Durable IP65 weatherproof enclosure along with 15kV ESD and 6kV lightning protection ensures all-weather suitability • Pharos Control gives administrators a free, centralized management system • Passive PoE supports to allow flexible deployment and convenient installation 	2
F	Network Point Capling	CAT6A cable up to 1 Giga speed	350M
G	Pipes for cabling	PVC Pipes for network cable installation outdoor /indoor ...25mm	180M
J	Installation and programming	<p>يشمل التحفير بالارض / installation pipes and cabling and camera , and system configuration</p> <p>. لتأسيس الكوابل لمسافة 60 متر والعمل حسب الاصول المدنية والانشائية</p>	1