

ILS Z RWY 08L



NM to DME	IQAN	8	7	6	5	4	3	2	TRANSITION ALTITUDE 13000 TRANSITION LEVEL FL 150	
ALTITUDE		4960	4630	4300	3970	3640	3320	3000		

MISSED APPROACH:

Climb to **ENADA** on course **075°M** (MAX 250 kt IAS) at **6000** (3639) and hold or follow ATC instructions.

If unable to reach holding altitude, continue to climb in the holding.

OCA (H)	A	B	C	D	DL
CAT I 2.5%	2600 (239)	2610 (249)	2620 (259)	2630 (269)	2630 (269)
CAT I 3.0%	2510 (149)	2530 (169)	2540 (179)	2550 (189)	2550 (189)
CAT II 2.5%	2510 (149)	2530 (169)	2540 (179)	2550 (189)	2550 (189)
CAT II 3.0%	2420 (59)	2430 (69)	2450 (89)	2470 (109)	2470 (109)
GP INOP	2750 (389)				-

CIRCLING	A	B	C	D	DL
	3020 (659)	3310 (949)	3500 (1139)		-

GS	kt	70	85	100	115	130	145	160	185
FAF-MAPT 7.3 NM	min:s	6:17	5:10	4:24	3:49	3:23	3:02	2:45	2:23
Rate of descent	ft/min	370	450	530	610	690	770	850	980

Holding instruction

<i>Path Descriptor</i>	<i>Waypoint Identifier</i>	<i>Inbound Course °M (°T)</i>	<i>Leg Distance</i>	<i>Turn direction</i>	<i>Minimum Altitude (ft/FL)</i>	<i>Maximum Altitude (ft/FL)</i>	<i>Speed Limit (kt)</i>	<i>Magnetic Variation</i>	<i>Navigation Specification</i>
Hold	ORNAV	260 (265.0)		L	6000	10000	220	+5.0	RNAV 1
Hold	OBTEL	165 (170.0)		R	6000	10000	220	+5.0	RNAV 1
Hold	TULEN	345 (350.0)		L	6000	12000	220	+5.0	RNAV 1

Route Description: IAC RNP ILS Z RWY 08L

RNP ILS Z RWY 08L											
<i>Serial Number</i>	<i>Path Descriptor</i>	<i>Waypoint Identifier</i>	<i>Fly - Over</i>	<i>Course °M (°T)</i>	<i>Magnetic Variation</i>	<i>Distance (NM)</i>	<i>Turn direction</i>	<i>Altitude (ft/FL)</i>	<i>MAX IAS (kt)</i>	<i>VPA/TCH (°ft)</i>	<i>Navigation Accuracy (NM)</i>
10	IF	OBTEL	-	-	-	-	-	+6000	-230	-	RNP APCH
20	TF	TAPNO	-	165 (170.3)	+5.0	5.0	-	+5500	-210	-	RNP APCH
10	IF	TULEN	-	-	-	-	-	+6000	-250	-	RNP APCH
20	TF	AI422	-	345 (350.3)	+5.0	5.0	-	-	-230	-	RNP APCH
30	TF	TAPNO	-	345 (350.3)	+5.0	5.8	-	+5500	-210	-	RNP APCH
10	IF	ORNAV	-	-	-	-	-	+6000	-250	-	RNP APCH
20	TF	AI422	-	260 (264.5)	+5.0	5.0	-	-	-230	-	RNP APCH
30	TF	TAPNO	-	345 (350.3)	+5.0	5.8	-	+5500	-210	-	RNP APCH
10	IF	TAPNO	-	-	-	-	-	+5500	-210	-	RNP APCH
20	TF	AI407	-	075 (080.3)	+5.0	4.4	-	+5000	-	-	RNP APCH
30	TF	RW08L	Y	075 (080.3)	+5.0	7.9	-	@2416	-	-3.0/ 55	RNP APCH
40	CF	ENADA	Y	075 (080.5)	+5.0	12.4	-	+6000	-250	-	RNP APCH
50	HM	ENADA	Y	265 (270.0)	+5.0	4.5	R	-10000 +6000	-220	-	RNP 1

Aeronautical Data Tabulation: IAC RNP ILS Z RWY 08L

WAYPOINT LIST		
Waypoint / Fix	Latitude	Longitude
OBTEL	31°46'28.170"N	035°42'56.686"E
TAPNO	31°41'31.856"N	035°43'56.172"E
TULEN	31°30'50.349"N	035°46'04.661"E
AI422	31°35'46.683"N	035°45'05.370"E
ORNAV	31°36'15.421"N	035°50'55.033"E
AI407	31°42'16.031"N	035°48'59.611"E
RW08L	31°43'36.228"N	035°58'10.088"E
ENADA	31°45'40.610"N	036°12'29.570"E