

Phone: +962 6 4872681
Fax: +962 6 4891266
AFS: OJAMYHYX
E-mail: ais.hq@carc.gov.jo

THE HASHEMITE KINGDOM OF JORDAN
CIVIL AVIATION REGULATORY COMMISSION
DIRECTORATE OF AIR TRAFFIC MANAGEMENT
AERONAUTICAL INFORMATION SERVICES
HEADQUARTERS
P.O.BOX: 7547 – AMMAN

AIP
SUP 05/ 23
27 NOV 2023

05/23

Until 2411011200, Low Visibility Procedures (LVP) at Amman/Queen Alia Aerodrome

REF AIP JORDAN page AD 1.1-3, AD 1.1-4 and AD 1.1-5 dated 01 MAY 2019 AMEND to read:

1- Para 1.1.3.3.1:

The preparation phase shall be commenced when; 1) any of the RVR readings are below (1500 M), and/or 2) cloud base are between (400-200 FT). In the preparation phase, CAT II operations are expected.

2- Para 1.1.3.3.2:

The operation of the low visibility procedure shall be commenced when:

a) Runway (26R/08L): 1) TDZ RVR is less than (550 M) and equal/or greater than (300 M), and/or 2) cloud base is less than (200 FT) but not less than (120 FT). Traffic is approved for landing.

b) Runway (26L): 1) TDZ RVR is less than (550 M) and equal/or greater than (400 M), and/or 2) cloud base is less than (200 FT) but not less than (140 FT). Traffic is approved for landing.

Note: LVP for Runway (08R) is not applicable (CAT II precision approach is not Available).

3- Para 1.1.3.3.4:

For Runway (26R/08L): “follow-me” service is provided upon pilot request to guide the aircraft to/from stands whenever RVR is (550 M) and below.

For Runway (26L): “follow-me” service shall be provided to guide the aircraft to/from stands whenever RVR is (550 M) and below.

4- Para 1.1.3.4.1: LVTO, for Runway (26R/08L) and Runway (26L), shall be commenced when the RVR is less than (300 M) and equal/or greater than (150 M).

Delete a and b. and keep the note.

5- Para 1.1.3.4.2:

For Runway (26R/08L): only one departure aircraft in the North apron is allowed to maneuver in the apron. And

For Runway (26L): only one departure aircraft in the South apron is allowed to maneuver in the apron.

6- Add :

Para 1.1.3.5.5: Pilots shall report when entering Taxiway (A) or Taxiway (H) while taxiing out for departure.

7- Para 1.1.3.6.2:

e) Runway lighting.

8- AD 1.1.4: Aerodrome operating minima:

Para 1.1.4.1: Take off weather minimum for IFR flights using Amman/Marka and Aqaba/King Hussein International Aerodromes is RVR 400M

Para 1.1.4.2: Take off weather minimums for IFR flights using Amman/Queen Alia International Aerodrome are as follows:

- For Runway 08R is RVR 400M

- LVTO for Runways 26R/08L and 26L for all ACFT category, RVR minimum is (150 M).

AIS HEADQUARTERS

